

# POD3 CONFIGURATIONS

Gabriel | Nathan | Thibaud

# tour des configurations

1

VUE D'ENSEMBLE

2

SWITCH 1 (S1POD3GL)

3

SWITCH 2 (S1POD3GL)


4

SWITCH DE DISTRIBUTION (S3POD3GL)

5

ROUTEUR (R0POD3GL)

# vue d'ensemble



## VLAN's :

VLAN DATA31 : 172.16.31.0 /24

VLAN GESTION2 : 172.16.32.0 /24

VLAN NATIF : 172.16.30.0 /24




SWITCH I

S1POD3GL

J

```
!### S1POD3GL (v0.4.210617)
! Hostname, MOTD, MDP
en
conf t
    hostname S1POD3GL
    banner motd " acces interdit sur S1POD3GL (v0.4.210617) "
    line 0
        password *****
        enable secret *****
        service password-encryption
end
! base de données VLAN + SVI
conf t
    vlan 300
        name NATIF
    vlan 311
        name DATA31
    vlan 312
        name GESTION2
int vlan 312
    description management interface of device (S1POD3GL)
    ip add 172.16.32.1 255.255.255.0
    no shutdown
    exit
    ip default-gateway 172.16.32.252
end
```

```
###  
###  
*  
  
###  
  
! allocation access/trunk interfaces ####  
conf t  
interface range fa0/1-24  
description UNUSED administratively down  
shutdown  
interface range gi0/1-2  
description UNUSED administratively down  
shutdown  
interface range fa0/1-2  
description TRUNK-link LAN-side (POD3GL)  
switchport trunk native vlan 300  
switchport trunk allowed vlan 311,312  
switchport mode trunk  
no shutdown  
interface fa0/3  
description interface LAN for PC SHS  
switchport mode access  
switchport access vlan 312  
no shutdown
```




SWITCH 2

S2POD3GL



```
!### S2POD3GL (v0.4.210617)                                ###
! Hostname, MOTD, MDP
en
conf t
    hostname S2POD3GL
    banner motd " acces interdit sur S2POD3GL (v0.4.210617) "
    line 0
        password *****
        enable secret ****
        service password-encryption
end
! ### base de données VLAN + SVI
conf t
    vlan 300
        name NATIF
    vlan 311
        name DATA31
    vlan 312
        name GESTION2
int vlan 312
    description management interface of device (S2POD3GL)
    ip add 172.16.32.2 255.255.255.0
    no shutdown
    exit
ip default-gateway 172.16.32.252
exit
end
```

```
###                                ###
###                                ###
! ### allocation access/trunk interfaces      ###
conf t
    interface range fa0/1-24
        description UNUSED administratively down
        shutdown
    interface range gi0/1-2
        description UNUSED administratively down
        shutdown
    interface range fa0/1-2
        description TRUNK-link LAN-side (POD3GL)
        switchport trunk native vlan 300
        switchport trunk allowed vlan 311,312
        switchport mode trunk
        no shutdown
end
```



SWITCH 3

S3POD3GL



```
!### S3POD3GL (v0.4.210617)
! Hostname, MOTD, MDP
en
conf t
    hostname S3POD3GL
    banner motd " acces interdit sur S3POD3GL (v0.4.210617) "
    line 0
        password *****
        enable secret ****
        service password-encryption
end
! ### base de données VLAN + SVI
conf t
    vlan 300
        name NATIF
    vlan 311
        name DATA31
    vlan 312
        name GESTION2
    int vlan 312
        description management interface of device (S3POD3GL)
        ip add 172.16.32.3 255.255.255.0
        no shutdown
        exit
        ip default-gateway 172.16.32.252
end
```

```
##  
! ### allocation access/trunk && interfaces  
###  
conf t  
    interface range gi0/0  
        description UNUSED administratively down  
        shutdown  
    interface range gi1/0/1-24  
        description UNUSED administratively down  
        shutdown  
    interface range te1/1/1-4  
        description UNUSED administratively down  
        shutdown  
    interface range Gi1/0/1-3  
        description TRUNK-link LAN-side (POD3GL)  
        switchport trunk native vlan 300  
        switchport trunk allowed vlan 311,312  
        switchport mode trunk  
        no shutdown  
end
```



ROUTER 0

ROPOD3GL



```
!### R0POD3GL (v0.4.210617) #####
! Hostname, MOTD, MDP #####
conf t
    hostname R0POD3GL
    banner motd " acces interdit sur R0POD3GL (v0.4.210617) "
    line 0
        password *****
        enable secret *****
        service password-encryption
end
! ### encapsulation dot1Q #####
conf t
    interface range Gi0/0-2
        description UNUSED administratively down
        shutdown
    interface Gi0/1.311
        description sub-interface for DATA31
        encapsulation dot1Q 311
        ip add 172.16.31.252 255.255.255.0
        no shutdown
    interface Gi0/1.312
        description sub-interface for GESTION2
        encapsulation dot1Q 312
        ip add 172.16.32.252 255.255.255.0
        no shutdown
    interface Gi0/1
        description interface LAN for server HP
!   ip add 172.16.31.x 255.255.255.0
!   no shutdown
end
|
```

# suite imminente:

config du SHS (vlan gestion)

config du HP (vlan gestion)

config STP

config ETHERCHANNEL

# FAQ / AMELIORATIONS ?

